
PUMP, CENTRIFUGAL, 600 GPM





Functional Description

The 600 GPM Pump is used as the lead pumping station, or boost pumping station, within the EWDS.

Technical Description

<u>Information</u>		<u>Fuel</u>	
Manufacturer:	W.S. Darley & Co	Туре:	Diesel/JP-8/F-24
Model:	LE600-W	Fuel Capacity (Gal):	23.0
		Fuel Consumption (GPH):	4.9
Shipping Dimensions		Operating Dimensions	
Length (in):	149.9	Length (in):	149.9
Width (in):	86.1	Width (in):	86.1
Height (in):	96.2	Height (in):	96.2
Square (ft²)/Cube (ft³):	89.6/718.5	Square (ft ²)/Cube (ft ³):	89.6/718.5
Weight (lbs)		Weight (lbs)	
Dry:	4,080.0	Wet (Coolant & POLs):	4,308.8
Alternative Model: B2394BB, 600 GPM Pump, NSN: 4320-01-589-1113			

<u>Alternative Model</u>: B2394BB, 600 GPM Pump, NSN: 4320-01-589-1113

<u>Associated TAMCNs</u>: B01377B, Expeditionary Water Distribution System.

<u>Transportability</u>: D00047K, Medium Tactical Vehicle (MTV), MK 23, MK 25.