BENCH TOP POWER SUPPLY (40VDC)



TAMCN: A7706

ID: 10244B

NSN: 6130-01-531-9927

-40°F to +185°F

Functional Description

The PP-8436/P (XHR-40-25CE) bench top power supply provides 1000 watts of DC power from worldwide power. It has front panel binding post connectors, rear panel bus bar outputs, and a low current requirement that allows it to be plugged into a standard 120 VAC, 15A circuits.

Technical Description

Power Supply		Dimensions	
Manufacturer:	Xantrex	Length (in):	18.6
Model:	XHR-40-25CE	Width (in): Height (in):	8.5 3.4
Power		Weight (lbs):	14
Input:	85-250 VAC	Volume (ft³):	0.4
Output:	0-40 VDC @ 0-25 Amp	<u>Temperatures</u> Operating:	32°F to 104°F

Storage:

Specifications

Frequency (Hz):

Input Harmonic Distortion: Harmonics distortion complies with EN61000-3-2 limits.

47-63

Time Delay: 4 sec maximum from power on until output stable.

The PP-8436/P will operate from worldwide power. However, it is only fielded with a 120VAC input power cable.

NOTES: There are three (3) power supplies associated with TAMCN A7706. Xantrex model XHR-40-25M, NSN 6130-21-911-6149 is no longer being fielded. When no longer repairable Xantrex model XHR-40-25CE, NSN 6130-01-531-9927 or Ametek XHR40-25M106, NSN 6130-01-593-9105 will be provided..