

AIR CONDITIONER, 5-TON, 60,000 BTU/hr	
	TAMCN: B0008
	ID: 11084B
	NSN: 4120-01-581-2260
Functional Description	
<p>The Air Conditioner, 5-Ton, 60,000 BTU/hr, is a packaged system designed to provide conditioned air to a shelter or van. The 5-Ton ECU is controlled with a built-in control box or remote controller and operates using 208VAC 3-phase 50/60 Hz power supplied by a generator or shore power via a power plug located on the ECU. The refrigerant system uses R-22 or R-407c refrigerant and has a cooling capacity at 60Hz of not less than 60,000 BTU/hr at 95°F ambient outside temperature. The heating system is furnished with a 37,000 BTU/hr resistive type heater in addition to fan heat.</p>	
Technical Description	
<p>Unit Manufacturer: HDT Nordic Air, Inc. Model: GL0583ZAADWYX01</p>	<p>Dimensions Depth (in): 37 Width (in): 47.62 Height (in): 47.44 Weight (lb): 575 Volume (ft³): 48.35 Horizontal/Vertical: Horizontal</p>
<p>Power Req. Frequency (Hz): 60 Voltage (Volts): 208 Phase: 3 Wires: 4-Wire Max Power Consumption: 11kW</p>	<p>Capacity Refrigerant: R-22 or R-407c Max. Ambient Temperature: 125°F Min. Ambient Cooling: 50°F Min. Ambient Heating: -25°F</p>
<p>Capacity Cooling (BTU/hr): 60,000 Heating (BTU/hr): 37,000 CFM: 2000 Duct Size: (1) 16 in. for Supply (1) 16 in. for Return</p>	
Alternate Models	TAMCN: B0008, ID: 11084A, NSN: 4120-01-526-1060
Replaced Items	B0007, B0011
Transportability	Forklift Portable.