

MEPDIS-REPLACEMENT, POWER DISTRIBUTION BOX, 15kW													
	TAMCN: B0029												
	ID: 11183A												
	NSN: 6110-01-532-1764												
Functional Description													
<p>The 15kW Power Distribution Box (PDB) is a component of the Mobile Electric Power Distribution-Replacement (MEPDIS-R) system. MEPDIS-R is designed to provide electrical power distribution in a field environment. The MEPDIS-R system provides a flexible, modular, recoverable, safe power distribution capability that can be quickly emplaced and recovered for later reuse. The 15kW PDB has two 60A input connectors to permit load paralleling and load transfer. The 15kW PDB provides (4) 30A 3-phase, (4) 20A single-phase output connectors, and a covered duplex receptacle.</p>													
Technical Description													
<table border="0"> <thead> <tr> <th style="text-align: left;">Panel</th> <th style="text-align: left;">Dimensions</th> </tr> </thead> <tbody> <tr> <td>Manufacturer: LEX Products</td> <td>Length (in): 26</td> </tr> <tr> <td>Model: DB-60MA-F22QS3</td> <td>Width (in): 23</td> </tr> <tr> <td>Voltage (Volts): 120/208</td> <td>Height (in): 17</td> </tr> <tr> <td>Frequency (Hz): 60</td> <td>Weight (lbs): 83</td> </tr> <tr> <td>Phase: 1 and 3</td> <td>Volume (ft³): 5.8</td> </tr> </tbody> </table>	Panel	Dimensions	Manufacturer: LEX Products	Length (in): 26	Model: DB-60MA-F22QS3	Width (in): 23	Voltage (Volts): 120/208	Height (in): 17	Frequency (Hz): 60	Weight (lbs): 83	Phase: 1 and 3	Volume (ft ³): 5.8	
Panel	Dimensions												
Manufacturer: LEX Products	Length (in): 26												
Model: DB-60MA-F22QS3	Width (in): 23												
Voltage (Volts): 120/208	Height (in): 17												
Frequency (Hz): 60	Weight (lbs): 83												
Phase: 1 and 3	Volume (ft ³): 5.8												
Technical Data													
<p>Input: 2 Each: 5-Wire, 3-Phase 60 Amp. Lamps on each phase. IEC 309 Pin & Sleeve Commercial Male Connector. Both inputs are circuit breaker protected.</p> <p>Outputs: 4 Each: 5-Wire, 3-Phase, 30 Amp IEC 309 Pin & Sleeve receptacle. 4 Each: 3-Wire, 1-Phase, 20 Amp IEC 309 Pin & Sleeve receptacle. 1 GFCI Covered Duplex Receptacle, 120VAC, 1-Phase. All circuit breaker protected.</p>													
Replaced Item	15kW MEPDIS (B0595).												
Transportability	Two Handle, Portable.												