

HIGH SPEED, HIGH MOBILITY, (HSHM) CRANE
TAMCN: B0443



TC-350

National Stock Number/ID Number	
3810-01-268-1737 (w/o Pile Driver Capability)	09109A
3810-01-320-1920	09109B

DESCRIPTION AND FUNCTION

The High Speed, High Mobility (HSHM) Crane (NSN: 3810-01-268-1737) is a diesel-powered, rubber-tired crane with a hydraulic boom. It is capable of all general crane operations, clamshell, container handling and general lifting up to 50,000 pounds. It is capable of operating over rough terrain. The Heavy Crane attachments include: Bucket, Concrete (TAMCN: B0176) and Bucket, Clamshell (TAMCN: B0171).

TECHNICAL DESCRIPTION

Manufacturer: P&H Crane

OPERATING AND SHIPPING DATA

Operating Mode

Weight: 69,825 lb (31,672 kg)
 Width: 102 in. (259 cm)
 Length: 499.8 in. (1,269 cm)
 Height: 136.9 in. (348 cm)
 Cube: 4,097.8 ft³ (116.04 m³)
 Square Stowage: 354 ft² (32.89 m²)

Shipping Mode

Weight: 69,825 lb (31,672 kg)
 Width: 102 in. (259 cm)
 Length: 499.8 in. (1,269 cm)
 Height: 136.9 in. (348 cm)
 Cube: 4,097.8 ft³ (116.04 m³)
 Square Stowage: 354 ft² (32.89 m²)

Capacity

Fuel Consumption per Hour: 7 gph
 Lift Capacity: 50,000 lb

Replaced Item(s) 30 Ton Drott Crane

Transportability Air, rail, and highway transportable. Can utilize M870 trailer to transport

Associated TAMCN(s) B0176, B0171, U0004