## ENHANCED ENVIRONMENTAL CONTROL UNIT, 0.75-TON, 9,000 BTU/hr, 60 Hz





The Enhanced Environmental Control Unit (E2CU), 0.75 Ton, 9,000 BTU/hr Shelter Mounted E2CU is capable of providing complete environmental control, to include cooling, heating, dehumidification and filtering for various types of portable military shelters or tactical vehicles. The 0.75 Ton E2CU addresses the specialized requirement that certain units in the Marine Corps have for a highly mobile environmental control capability.

| <u>Information</u>       |                     |             |                | <u>Dimensions</u>                                  |         |
|--------------------------|---------------------|-------------|----------------|--|---------|
| Manufacturer:            | HDT                 |             |                | Length (in):                                       | 26.0    |
| Model:                   | GSQ396ZABNWFX11     |             |                | Width (in):  | 23.8    |
| Power                    |                     |             |                | Height (in):                                       | 16.0    |
| Input                    |                     |             |                | Weight (lbs):                                      | 155.0   |
| AC:                      | 120 VAC, 50/60Hz    |             |                | Square (ft <sup>2</sup> )/Cube (ft <sup>3</sup> ): | 4.3/5.7 |
| Phase:                   | Single-Phase        |             |                | <u>Environmental</u>                               |         |
|                          |                     |             |                | <u>Limitations</u>                                 |         |
| Wires (AWG):             | 3-Wire/8            |             |                | Refrigerant:                                       | R-410A  |
| Connector                |                     |             | 20             | Max. Ambient Cooling                               | 130.0   |
| (AMP):                   |                     |             |                | (°F):  |         |
|                          |                     |             |                | Min. Ambient Cooling (°F):                         | 45.0    |
| <b>Environmental</b>     | <b>Current Draw</b> | Power Draw  | <u>Capacit</u> | Min. Ambient Heating (°F):                         | -25.0   |
| <b>Ambient Condition</b> | (Amps)              | <u>(kW)</u> | (BTU/h         |  |         |
| Cooling at 95°F:         | 14.1                | 1.635       | 10,200         |  |         |
| Cooling at 125°F:        | 17.5                | 2.023       | 9,100          |  |         |
| Heating:                 | 17.2                | 1.993       | 5,600          |  |         |

**<u>Transportability</u>**: Transported with supported shelter or as secured cargo.